

TECHNICAL DATA		50 Hz	60 Hz
• Power	kW - HP	7,5 - 10	not available
• Input voltages ^{1) 2)} Current settings available	V A	---	not available
		345D ... 415D 15,1D	not available
• Electrical cable length Electrical plug type		9 meters 4 poles (5 poles upon request)	
• ATEX mark		NO ATEX	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}		IP 55 F IE1	
• Maximum vacuum Optimum vacuum ³⁾	mmH ₂ O	4.200 2.500	not available
• Maximum air flow	l/min - m ³ /h	13.500 - 810	not available
• Acoustic level ^{d)}	dB (A)	78	not available
• Dust Bin: capacity wheels diameter	l mm	90 60	
• Diameters: material inlet wheels ⁴⁾ (front - rear)	mm	100 200 - 150	
• Dimensions: L x W x H (H.005 - H.008) Weight	mm kg	1.285 x 650 x 1.772 (1.982 - 2.072) 200	
• Packing size ⁵⁾ : L x W x H (H.005 - H.008) Weight	mm kg	1.500 x 800 x 2.000 (2.100 - 2.190) 220	
• Primary filter		Star filter	
Surface area Diameter	cm ² - m ² mm	35.000 - 3,5 560	
Dust Class ^{6) e)} Media ⁷⁾		L Polyester	
Filter cleaning ⁸⁾		Ergonomic manual shaker	
• Automatic filter cleaning - Optional		Cartridges kit	
Surface area Nominal output	cm ² - m ² m ³ /h	94.800 - 9,48 3.410	
Dust Class ^{e)} Media		M Antistatic polyester	
Compressed air consumption pressure	nl/min bar	48 4 ÷ 6	
• Upstream absolute filter - Optional		HEPA 14	
Surface area Nominal output	cm ² - m ² m ³ /h	120.000 - 12 1.200	
Dust Class ^{f)} Media		H14 Glass fibre	
Efficiency M.P.P.S. ^{f)} (with 0,18 µm particles)		99,995%	
• Downstream absolute filter - Optional		---	
Surface area Nominal output	cm ² - m ² m ³ /h	---	
Dust Class ^{f)} Media		---	
Efficiency M.P.P.S. ^{f)} (with 0,18 µm particles)		---	

Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

AVAILABLE VERSIONS

• KB7P.9006	90 litres three phase vacuum dust collector
--------------------	---

OPTIONS

		Basic	Pharma ⁹⁾
• 001	AISI 304 stainless steel dust bin		
• 002	AISI 304 stainless steel dust bin and filtering chamber		
• 003	Entirely made out of AISI 304 stainless steel	upon request	upon request
• 004	Liquids switch off		
• 005	Upstream absolute filter (HEPA) with M class primary filter - version: painted AISI 304 stainless steel		
• 045	Downstream absolute filter (HEPA) with M class primary filter - version: painted AISI 304 stainless steel		
• 006	Electric filter shaker with push button		
• 008	Automatic filter cleaning (cartridge kit)		
• 075	Dust bin overfilling switch off		
•	Overheating safety relief valve	included	included
• 9006	Color gray RAL 9006 painted housing	included	included
•	On/off arrangement through clean contacts supplied by processing machine		



- ¹⁾ Other input voltages upon request
- ²⁾ **Default factory setting: 400 V - 50 Hz**
- ³⁾ Maximum vacuum in continuous run
- ⁴⁾ Marks proof wheels with bearings
- ⁵⁾ Standard packing size
- ⁶⁾ M dust class filters available upon request
- ⁷⁾ Other materials available according to the material to be vacuumed
- ⁸⁾ Electric filter shaker with push-button as option
- ⁹⁾ AISI 316L cleaned welding and inner mirror polished

For an effective and proper use according to your application requirements, please see our accessories and spare parts catalogue.

Versions available: **L-M-H** filtration (for hazardous powders vacuuming) certification
ATEX certified machines