

TECHNICAL DATA			50 Hz	60 Hz
• Power	kW - HP		0,4 - 0,54	0,5 - 0,67
• Input voltages ^{1) 2)} Current settings available	V A		345Y ... 415Y 1,5Y 200D ... 240D 2,6D	380Y ... 480Y 1,5Y 220D ... 275D 2,6D
• Electrical cable length Electrical plug			6 meters Not supplied	
• ATEX mark			NO ATEX	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}			IP 55 F IE1	
• Maximum vacuum Optimum vacuum ³⁾	mmHg		1.600 1.200	2.000 1.500
• Maximum air flow	l/min - m³/h		1.334 - 80	1.550 - 93
• Acoustic level ^{d)}	dB (A)		63	64
• Dust Bin: capacity	l		9	
• Diameters: material inlet	mm		40	
• Dimensions: L x W (W.090) x H Weight	mm kg		650 x 350 (380) x 480 21	
• Packing size ⁵⁾ : L x W (W.090) x H Weight	mm kg		821 x 671 (671) x 650 26	
• Primary filter			Bag filter	
Surface area Diameter	cm² - m² mm		2.300 - 0,23 280	
Dust Class ^{6) e)} Media ⁷⁾			L Polyester	
Filter cleaning ⁸⁾			Not available	
• Automatic filter cleaning - Optional			---	
Surface area Nominal output	cm² - m² m³/h		---	
Dust Class ^{e)} Media			---	
Compressed air consumption pressure	nl/min bar		---	
• Upstream absolute filter - Optional			HEPA 13	
Surface area Nominal output	cm² - m² m³/h		12.000 - 1,2 ---	
Dust Class ^{f)} Media			H13 Glass fibre	
Efficiency M.P.P.S. ^{f)} (with 0,18 µm particles)			99,95%	



¹⁾ Other input voltages upon request

²⁾ Default factory setting: 400 V - 50 Hz

³⁾ Maximum vacuum in continuous run

⁴⁾ ---

⁵⁾ Standard packing size

⁶⁾ M dust class filters available upon request

⁷⁾ Other materials available according to the material to be vacuumed

⁸⁾ ---

⁹⁾ AISI 316L cleaned welding and inner mirror polished

Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

AVAILABLE VERSIONS

• KH0528	9 litres three phase vacuum dust collector
----------	--

OPTIONS

• 001	AISI 304 stainless steel dust bin
•	AISI 316L stainless steel dust bin, "pharma finishing" ⁹⁾
• 003	AISI 304 stainless steel completely made
•	AISI 316L stainless steel completely made, "pharma finishing" ⁹⁾
• 005	Upstream absolute filter (HEPA) with M class primary filter
•	Overheating safety relief valve
•	Silencer for painted version
•	Silencer for stainless steel version (.003)
• 090	On/off switch with thermal protection
• 100	Fitted with single-phase vacuum unit

For an effective and proper use according to your application requirements, please see our accessories and spare parts catalogue.

Versions available: L-M-H filtration (for hazardous powders vacuuming) certification
ATEX certified machines