



TECHNICAL DATA		50 Hz	60 Hz
• Power	kW - HP	25,0 - 34,0	29,0 - 39,44
• Input voltages ^{1) 2)} Current settings available	V A	---	---
		345D ... 415D 52,0D	380D ... 480D 52,0D
• Electrical cable length Electrical plug		9 meters Not supplied	
• ATEX mark		 II 3D - Ex c t IIIB T135°C Dc	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}		IP 55 F IE1	
• Maximum vacuum Optimum vacuum ³⁾	mmHg	4.400 3.100	4.700 2.700
• Maximum air flow	l/min - m³/h	34.166 - 2.050	40.833 - 2.450
• Acoustic level ^{d)}	dB (A)	78	79
• Dust bin: capacity wheels diameter	l mm	175 100	
• Diameters: material inlet wheels ⁴⁾ (front - rear)	mm	100 250 - 200	
• Dimensions: L x W x H (H.008) Weight	mm kg	2.020 x 887 x 2.166 (2.166) 715	
• Packing size ⁵⁾ : L x W x H (H.008) Weight	mm kg	2.100 x 950 x 2.340 (2.340) 735	
• Primary filter		Star filter	
Surface area Diameter	cm² - m² mm	109.000 - 10,9 780	
Dust Class ^{6) e)} Media ⁷⁾		M Antistatic polyester	
Filter cleaning ⁸⁾		Electric filter shaker with push-button	
• Automatic filter cleaning - Optional		---	
Surface area Nominal output	cm² - m² m³/h	---	
Dust Class ^{e)} Media		---	
Compressed air consumption pressure	nl/min bar	---	
• Upstream absolute filter - Optional		HEPA 14	
Surface area Nominal output	cm² - m² m³/h	260.000 - 26,0 2.600	
Dust Class ^{f)} Media		H14 Glass fibre	
Efficiency M.P.P.S. ^{f)} (with 0,18 µm particles)		99,995%	

¹⁾ Other input voltages upon request

²⁾ **Default factory setting: 400 V - 50 Hz**

³⁾ Maximum vacuum in continuous run

⁴⁾ Antistatic wheels

⁵⁾ Standard packing size

⁶⁾ PTFE coated antistatic star filter available upon request

⁷⁾ Other materials available according to the material to be vacuumed

⁸⁾ **Electric filter shaker with push-button included**

Normatives: a) IEC60529; b) IEC60085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

AVAILABLE VERSIONS

• **K25P.022B** 175 litres three phase vacuum cleaner - IP55 - ATEX zone 22

OPTIONS

• 001	AISI 304 stainless steel dust bin (instead of the painted one)	
• 002	AISI 304 stainless steel dust bin and filtering chamber	
• 003	Entirely made out of AISI 304 stainless steel	upon request
• 004	Liquids switch off	not available
• 005	Upstream absolute filter (HEPA) - version: painted AISI 304 stainless steel	upon request
• 006	Electric filter shaker with push-button	included
• 008	Automatic reverse jet cartridge filtering system	not available
• 066	Dust bin overfilling switch off	
•	Reinforced dust bin	
•	On/off arrangement through micro-switch	
•	Overheating safety relief valve	included

For an effective and proper use according to your application requirements, please see our accessories and spare parts catalogue.
Versions available: • **L-M-H** filtration (for hazardous powders vacuuming) certification

