

TECHNICAL DATA		50 Hz	60 Hz
• Power	kW - HP	1,6 - 2	2,1 - 2,81
• Input voltages ^{1) 2)} Current settings available	V A	345Y ... 415Y 4,3Y 200D ... 240D 7,5D	380Y ... 480Y 4,4Y 220D ... 275D 7,6D
• Electrical cable length Electrical plug		6 meters Not supplied	
• ATEX mark		NO ATEX	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}		IP 55 F IE1	
• Maximum vacuum Optimum vacuum ³⁾	mmH ₂ O	2.600 2.000	2.850 2.200
• Maximum air flow	l/min - m ³ /h	3.600 - 216	4.166 - 250
• Acoustic level ^{d)}	dB (A)	69	70
• Dust Bin: capacity	l	25	
• Diameters: material inlet	mm	50	
• Dimensions: L x W (W.090) x H Weight	mm kg	830 x 460 (460) x 1.000 39	
• Packing size ⁵⁾ : L x W (W.090) x H Weight	mm kg	871 x 671 (671) x 1.200 44	
• Primary filter		Star filter	
Surface area Diameter	cm ² - m ² mm	7.000 - 0,7 360	
Dust Class ^{6) e)} Media ⁷⁾		L Polyester	
Filter cleaning ⁸⁾		Ergonomic manual shaker	
• Automatic filter cleaning - Optional		---	
Surface area Nominal output	cm ² - m ² m ³ /h	---	
Dust Class ^{e)} Media		---	
Compressed air consumption pressure	nl/min bar	---	
• Upstream absolute filter - Optional		HEPA 14	
Surface area Nominal output	cm ² - m ² m ³ /h	17.000 - 1,7 ---	
Dust Class ^{f)} Media		H14 Glass fibre	
Efficiency M.P.P.S. ^{f)} (with 0,18 µm particles)		99,995%	



- 1) Other input voltages upon request
- 2) **Default factory setting: 400 V - 50 Hz**
- 3) Maximum vacuum in continuous run
- 4) ---
- 5) Standard packing size
- 6) M dust class filters available upon request
- 7) Other materials available according to the material to be vacuumed
- 8) ---
- 9) AISI 316L cleaned welding and inner mirror polished

Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

AVAILABLE VERSIONS

• KH1636	25 litres three phase vacuum dust collector
-----------------	---

OPTIONS

• 001	AISI 304 stainless steel dust bin	
•	AISI 316L stainless steel dust bin, "pharma finishing" ⁹⁾	
• 003	AISI 304 stainless steel completely made	
•	AISI 316L stainless steel completely made, "pharma finishing" ⁹⁾	
• 005	Upstream absolute filter (HEPA) with M class primary filter	
•	Overheating safety relief valve	
•	Silencer for painted version	included
•	Silencer for stainless steel version (.003)	included
• 090	On/off switch with thermal protection	
• 100	Fitted with single-phase vacuum unit	

For an effective and proper use according to your application requirements, please see our accessories and spare parts catalogue.

Versions available: **L-M-H** filtration (for hazardous powders vacuuming) certification
ATEX certified machines