

TECHNICAL DATA		50 Hz	60 Hz
• Power (with ATEX certified vacuum unit)	kW - HP	2,6 - 3,5	3,1 - 4,2
• Input voltages ^{1) 2)} Current settings available	V A	360Y ... 440Y 6Y 210D ... 250D 10,4D	340Y ... 420Y 6,5Y 200D ... 240D 11,3D
• Electrical cable length Electrical plug		6 meters Not supplied	
• ATEX mark		 II 3D - Ex c t IIIC T135°C Dc	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}		IP 65 F IE1	
• Maximum vacuum Optimum vacuum ³⁾	mmHg	3.200 2.500	3.500 2.550
• Maximum air flow	l/min - m³/h	5.334 - 320	6.000 - 360
• Acoustic level ^{d)}	dB (A)	71	72
• Dust Bin: capacity	l	35	
• Diameters: material inlet	mm	70	
• Dimensions: L x W (W.090) x H Weight	mm kg	900 x 560 (560) x 1.025 55	
• Packing size ⁵⁾ : L x W (W.090) x H Weight	mm kg	950 x 671 (671) x 1.200 59	
• Primary filter		Star filter	
Surface area Diameter	cm² - m² mm	19.000 - 1,9 460	
Dust Class ^{6) e)} Media ⁷⁾		M Antistatic polyester	
Filter cleaning ⁸⁾		Ergonomic manual shaker	
• Automatic filter cleaning - Optional		---	
Surface area Nominal output	cm² - m² m³/h	---	
Dust Class ^{e)} Media		---	
Compressed air consumption pressure	nl/min bar	---	
• Upstream absolute filter - Optional		HEPA 14	
Surface area Nominal output	cm² - m² m³/h	52.000 - 5,2 600	
Dust Class ^{f)} Media		H14 Glass fibre	
Efficiency M.P.P.S. ^{f)} (with 0,18 µm particles)		99,995%	



¹⁾ Other input voltages upon request

²⁾ Default factory setting: 400 V - 50 Hz

³⁾ Maximum vacuum in continuous run

⁴⁾ ---

⁵⁾ Standard packing size

⁶⁾ PTFE coated antistatic star filter available upon request

⁷⁾ Other materials available according to the material to be vacuumed

⁸⁾ ---

⁹⁾ AISI 316L cleaned welding and inner mirror polished

Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

AVAILABLE VERSIONS

• **KH3046.022** 35 litres three phase vacuum dust collector - IP65 - ATEX zone 22

OPTIONS

• 001	AISI 304 stainless steel dust bin	included
•	AISI 316L stainless steel dust bin, "pharma finishing" ⁹⁾	
• 003	AISI 304 stainless steel completely made	
•	AISI 316L stainless steel completely made, "pharma finishing" ⁹⁾	
• 005	Upstream absolute filter (HEPA)	
•	Overheating safety relief valve	included
•	Silencer for painted version	included
•	Silencer for stainless steel version (.003)	included
• 090	On/off switch with thermal protection	
• 100	Fitted with single-phase vacuum unit	not available

For an effective and proper use according to your application requirements, please see our accessories and spare parts catalogue.

Versions available: **L-M-H** filtration (for hazardous powders vacuuming) certification