



TECHNICAL DATA		50 Hz	60 Hz
• Power	kW - HP	5,5 - 7,5	6,3 - 8,44
• Input voltages ^{1) 2)} Current settings available	V A	360Y ... 440Y 11,6Y 200D ... 240D 20,0D	380Y ... 480Y 11,6Y 220D ... 275D 20,0D
• Electrical cable length Electrical plug		9 meters Not supplied	
• ATEX mark		 II 3D - Ex c t IIIB T135°C Dc	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}		IP 55 F IE1	
• Maximum vacuum Optimum vacuum ³⁾	mmH ₂ O	5.100 4.450	5.100 4.300
• Maximum air flow	l/min - m ³ /h	5.334 - 320	6500 - 390
• Acoustic level ^{d)}	dB (A)	75	76
• Dust bin: capacity wheels diameter	l mm	90 - 50 60	
• Diameters: material inlet wheels ⁴⁾ (front - rear)	mm	70 200 - 150	
• Dimensions: L x W x H (H.008) Weight	mm kg	990 x 650 x 1.440 (1.770) 140	
• Packing size ⁵⁾ : L x W x H (H.008) Weight	mm kg	1.120 x 730 x 1.560 (1.900) 155	
• Primary filter		Star filter	
Surface area Diameter	cm ² - m ² mm	19.500 - 1,95 460	
Dust Class ^{6) e)} Media ⁷⁾		M Antistatic polyester	
Filter cleaning ⁸⁾		Manual filter shaker	
• Automatic filter cleaning - Optional		Cartridges kit	
Surface area Nominal output	cm ² - m ² m ³ /h	56.400 - 5,64 2.030	
Dust Class ^{e)} Media		M Antistatic polyester	
Compressed air consumption pressure	nl/min bar	48 4 ÷ 6	
• Upstream absolute filter - Optional		HEPA 14	
Surface area Nominal output	cm ² - m ² m ³ /h	28.000 - 2,8 480	
Dust Class ^{f)} Media		H14 Glass fibre	
Efficiency M.P.P.S. ^{f)} (with 0,18 µm particles)		99,995%	

¹⁾ Other input voltages upon request

²⁾ Default factory setting: 400 V - 50 Hz

³⁾ Maximum vacuum in continuous run

⁴⁾ Antistatic wheels

⁵⁾ Standard packing size

⁶⁾ PTFE coated antistatic star filter available upon request

⁷⁾ Other materials available according to the material to be vacuumed

⁸⁾ Electric filter shaker with push-button available as optional

Normatives: a) IEC60529; b) IEC60085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

AVAILABLE VERSIONS

• **KB5S.022B** 90 litres three phase vacuum cleaner - IP55 - ATEX zone 22

• **KB5S/50.022B** 50 litres three phase vacuum cleaner - IP55 - ATEX zone 22

OPTIONS		90 l.	50 l.
• 001	AISI 304 stainless steel dust bin (instead of the painted one)		
• 002	AISI 304 stainless steel dust bin and filtering chamber		
• 003	Entirely made out of AISI 304 stainless steel	upon request	upon request
• 004	Liquids switch off	not available	not available
• 005	Upstream absolute filter (HEPA)		
• 006	Electric filter shaker with push-button		
• 008	Automatic reverse jet cartridge filtering system		
• 066	Dust bin overfilling switch off	upon request	upon request
•	Reinforced dust bin	upon request	upon request
•	On/off arrangement through micro-switch	upon request	upon request
•	Overheating safety relief valve	included	included

For an effective and proper use according to your application requirements, please see our accessories and spare parts catalogue.
Versions available: • **L-M-H** filtration (for hazardous powders vacuuming) certification

